



US006017991A

United States Patent [19]
Drummond et al.

[11] **Patent Number:** **6,017,991**
[45] **Date of Patent:** **Jan. 25, 2000**

[54] **POLYOLEFIN FILM COMPOSITION AND
RESINS USEABLE THEREFORE AND
RELATED MAKING METHOD**

4,445,970 5/1984 Post et al. 162/135
5,089,200 2/1992 Chapman, Jr. et al. 264/127
5,866,646 2/1999 Radosta 524/451

[75] Inventors: **Donald Kendall Drummond**,
Quakertown; **Joseph Anthony Radosta**,
Easton; **Donald Richard Deutsch**,
Walnutport, all of Pa.

Primary Examiner—David W. Wu
Assistant Examiner—Ling Sui Choi
Attorney, Agent, or Firm—Marvin J. Powell; Terry B.
Morris

[73] Assignee: **Minerals Technologies Inc.**,
Bethlehem, Pa.

[21] Appl. No.: **09/131,494**

[22] Filed: **Aug. 10, 1998**

Related U.S. Application Data

[63] Continuation-in-part of application No. 08/934,761, Sep. 22,
1997, Pat. No. 5,866,646.

[51] **Int. Cl.**⁷ **C08K 3/34**

[52] **U.S. Cl.** **524/451**; 524/448; 524/445;
524/442

[58] **Field of Search** 524/451, 448,
524/445, 442

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,111,892 9/1978 Kamada et al. 524/412

[57] **ABSTRACT**

This invention concerns a mixture of a first component selected from talcs and one or more second component(s) selected from diatomaceous earth, natural and synthetic silica, clay, ceramic spheres, volcanic ash and glass cullet wherein the ratio of the component to the second component (s) provides an enhanced abrasiveness property, an enhanced die pressure character, and a reduced melt fracture character. The invention further relates to an antiblock agent made from such mixture that significantly reduces or eliminates the need to provide polymer processing additives. This invention also relates to a masterbatch composition having an admixture such that enhanced die pressure character and/or reduced melt fracture character are obtained.

8 Claims, No Drawings